

Declaration of Performance **Botament**

EKF500

Reference number of the Declaration of Performance: 9652770

1. Unique ID code of the product type	EKF500
2. Application(s)	Reactive resin adhesive DIN EN 12004 R2TE
3. Manufacturer	BOTAMENT GmbH Am Kruppwald 1 46238 Bottrop
4. Authorized representative	-
5. System of AVCP	System 3 System 4+ (for fire behaviour only)
6. Harmonised standard	EN 12004: 2007+A1: 2012
7. Notified body	Säurefliesner Vereinigung E.V. ID code NB 1212

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Initial shear adhesion strength	$\geq 2.0 \text{ N/mm}^2$	System 3	EN 12004: 2007 + A1: 2012
Shear adhesion strength after thermal shock	$\geq 2.0 \text{ N/mm}^2$		
Shear adhesion strength after water immersion	$\geq 2.0 \text{ N/mm}^2$		
Fire behaviour	E		
Release of chemicals dangerous to the environment and health	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra
Technical Director Botament

Bottrop, 14.09.2023
(place and date of issue)


(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.