

MULTIFUGE Diamond Max

Reference number of the Declaration of Performance: 9654524

1. Unique ID code of the product type	MULTIFUGE Diamond Max
2. Application(s)	Reactive resin adhesive internal and external use Increased requirements DIN EN 12004 R2T
3. Manufacturer	BOTAMENT GmbH Am Kruppwald 1 46238 Bottrop
4. Authorized representative	-
5. System of AVCP	System 3 System 4+ (for fire behaviour only)
6. Harmonised standard	EN 12004: 2007+A1: 2012
7. Notified body	Säurefliesner Vereinigung E.V. ID code NB 1212

8. Declared performances

Essential characteristic	Performance	harmonised technical specification
Initial shear adhesion strength	$\geq 2.0 \text{ N/mm}^2$	EN 12004: 2007 + A1: 2012
Shear adhesion strength after thermal shock	$\geq 2.0 \text{ N/mm}^2$	
Shear adhesion strength after water immersion	$\geq 2.0 \text{ N/mm}^2$	
Fire behaviour	E	
Release of chemicals dangerous to the environment and health	NPD	

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra
Technical Director Botament

Bottrop, 14.09.2023
(place and date of issue)


(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.