

MULTISTONE

Reference number of the Declaration of Performance: 4922400

1. Unique ID code of the product type	MULTISTONE
2. Application(s)	Cementitious mortar internal and external use Fast setting Increased requirements DIN EN 12004 C2FTE S1
3. Manufacturer	BOTAMENT GmbH Am Kruppwald 1 46238 Bottrop
4. Authorized representative	-
5. System of AVCP	System 3 System 4+ (for fire behaviour only)
6. Harmonised standard	EN 12004: 2007+A1: 2012
7. Notified body	Institut für Massivbau und Baustofftechnologie Universität Karlsruhe (TH) ID code 0754

8. Declared performances


Essential characteristic	Performance	AVCP	harmonised technical specification
Initial tensile adhesion strength	$\geq 1.0 \text{ N/mm}^2$	System 3	EN 12004: 2007 + A1: 2012
Tensile adhesion strength after heat ageing	$\geq 1.0 \text{ N/mm}^2$		
Adhesive tensile strength after water storage	$\geq 1.0 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 1.0 \text{ N/mm}^2$		
Fire behaviour	E		
Release of chemicals dangerous to the environment and health	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This Declaration of Performance is issued in accordance with Regulation (EU) No 305/2011 (amended by Commissions delegated Regulation (EU) No 574/2014), under the soleresponsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra
Technical Director Botament

Bottrop, 16.05.2024
(place and date of issue)


(signature)

Annex

According to Art. 6 (5) of the Regulation (EU) No. 305/2011 a Safety Data sheet according Regulation (EU) No. 1907/2006(REACH), Annex II is attached to this Declaration of Performance.