



**BOTAMENT**<sup>®</sup>

**SYSTEMBAUSTOFFE** 

DECLARATION OF PERFORMANCE  
according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

---

No 3410100

---

**BOTAMENT RD 1 Universal**

---

Liquid applied water impermeable dispersion product with enhanced crack bridging ability at low temperatures (-20°C) and resistant against contact with chlorine water

---

**BOTAMENT GmbH & Co.KG**  
**Am Kruppwald 1**  
**D - 46238 Bottrop**

---

System 3

---

14891:2012

---

MPA TU Braunschweig  
0761

---

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	system 3	14891:2012
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with lime water	no penetration		
Waterproofing	$\geq 0,75 \text{ mm}$		
Crack bridging ability at normal conditions	NPD		
Tensile adhesion strength after chlorine water contact	$\geq 0,5 \text{ N/mm}^2$		
Crack bridging ability at low temperatures (-5 °C)	$\geq 0,75 \text{ mm}$		
Crack bridging ability at very low temperatures (-20°C)	$\geq 0,75 \text{ mm}$		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

  
**BOTAMENT®**  
 SYSTEMBAUSTOFFE   
 GmbH & Co. KG  
 Am Kruppwerk 1 · D-48238 Bottrop  
 Tel. (0 20 4) 40 19 20 Fax 20 18 18  
 Bottrop 29.02.2016

Dr. Oliver Wowra  
 Leitung Technik