

DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No 3410060

BOTAMENT RD 2 The Green 1

Liquid applied water impermeable product for external installations on walls and floors,
beneath ceramic tiling

BOTAMENT GmbH & Co.KG
Am Kruppwald 1
D - 46238 Bottrop

System 3

14891:2012

MPA TU Braunschweig
0761

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	≥ 0,5 N/mm ²	system 3	14891:2012
Tensile adhesion strength after water contact	≥ 0,5 N/mm ²		
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²		
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm ²		
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm ²		
Waterproofing	no penetration		
Crack bridging ability at normal conditions	≥ 0,75 mm		
Tensile adhesion strength after chlorine water contact	≥ 0,5 N/mm ²		
Crack bridging ability at low temperatures (-5 °C)	NPD		
Crack bridging ability at very low temperatures (-20°C)	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

(name)

Bottrop, 18.01.2016

(place and date of issue)


BOTAMENT®
 SYSTEMBAUSTOFFE ■ ■ ■ ■
 GmbH & Co. KG
 Am Kruppweier 19 · D - 46285 Bottrop
 Tel. (0 20 41) 19 19-0 · Fax 25 24 13

(signature)