

DECLARATION OF PERFORMANCE

No 1

according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No 4461820

BOTAMENT MD 1 Speed

Liquid-applied water impermeable product for installations beneath ceramic tiling

BOTAMENT GmbH & Co.KG
Am Kruppwald 1
D - 46238 Bottrop
+49 (0)2041 101933
technik@botament.de

System 3

14891:2012


MPA TU Braunschweig
0761

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	$\geq 0,5 \text{ N/mm}^2$	system 3	14891:2012
Tensile adhesion strength after water contact	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after heat ageing	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after freeze-thaw cycles	$\geq 0,5 \text{ N/mm}^2$		
Tensile adhesion strength after contact with lime water	no penetration		
Waterproofing	$\geq 0,75 \text{ mm}$		
Crack bridging ability at normal conditions	$\geq 0,75 \text{ mm}$		
Tensile adhesion strength after chlorine water contact	$\geq 0,5 \text{ N/mm}^2$		
Crack bridging ability at low temperatures (-5 °C)	$\geq 0,75 \text{ mm}$		
Crack bridging ability at very low temperatures (-20°C)	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:



Dr. Oliver Wowra
Leitung Technik

BOTAMENT
SYSTEMBAUSTOFFE ■ ■ ■ ■
GmbH & Co. KG
Bottrop 31.07.2018
Am Kruppwald 1 · D - 46238 Bottrop
Tel. (0 20 41) 10 19-0 · Fax 26 24 13