

DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011
amended by Commissions delegated Regulation (EU) No 574/2014

No 4461952

Unique identification code of the product-type: BOTAMENT MD 2 The Blue 1

Intended use/es:

Liquid applied water impermeable product for external installations on walls and floors,
beneath ceramic tiling

Manufacturer:

BOTAMENT GmbH & Co.KG
Am Kruppwald 1
D - 46238 Bottrop

System/s of AVCP:

System 3

Harmonised standard:

14891:2012

Notified body/ies:

Materialprüfungs- und Forschungsanstalt Karlsruhe (MPA Karlsruhe)
Kennnummer 0754

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
Initial tensile adhesion strength	≥ 0,5 N/mm ²	System 3	14891:2012
Tensile adhesion strength after water contact	≥ 0,5 N/mm ²		
Tensile adhesion strength after heat ageing	≥ 0,5 N/mm ²		
Tensile adhesion strength after freeze-thaw cycles	≥ 0,5 N/mm ²		
Tensile adhesion strength after contact with lime water	≥ 0,5 N/mm ²		
Waterproofing	no penetration		
Crack bridging ability at normal conditions	≥ 0,75 mm		
Tensile adhesion strength after chlorine water contact	≥ 0,5 N/mm ²		
Crack bridging ability at low temperatures (-5 °C)	≥ 0,75 mm		
Crack bridging ability at very low temperatures (-20 °C)	≥ 0,75 mm		
Release of dangerous substances	NPD		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra
Head of Technik

Bottrop 27.04.2015


BOTAMENT®
 SYSTEMBAUSTOFFE ■ ■ ■ ■
 GmbH & Co. KG
 Arr Kluppwald 1 · D - 46238 Bottrop
 Tel. (0 20 41) 10 19-0 · Fax 26 24 13