

DECLARATION OF PERFORMANCE
according Annex III of the Regulation (EU) No 305/2011

Name of the product **BOTAMENT MS 20**

No. 4741070

1. Unique identification code of the product-type:

DIN EN 998-1

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Mineral-bound restoration render (white) for wet and salt-loaded surfaces

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

BOTAMENT GmbH & Co.KG
Am Kruppwald 1
D - 46238 Bottrop

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 4

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory Materialprüfanstalt für das Bauwesen Hannover, Betriebsstelle Clausthal, Zehntnerstr. 2a , 38678 Clausthal-Zellerfeld, identification number 0764, performed the determination of the product-type on the basis of type testing under system 4 and issued: test report 081094.1

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:

not relevant

9. Declared performance


Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	Class A1	DIN EN 998-1, Tab. 2
Water absorption	≥ 0.3 kg/m ³ after 24 h	
Water vapour permeability coefficient	μ ≤ 15	
Tensile bond strength	≥ 0,1 N/mm ² Fracture appearance B	
Thermal conductivity	0.27 W/m·K (tabular value)	
Durability (frost resistance)	Evaluation dependant on the determinations at the intended production site of the render	
Dangerous substances	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra
Leitung Technik

Bottrop, 07.05.2013


BOTAMENT®
 SYSTEMBAUSTOFFE ■ ■ ■ ■
 GmbH & Co. KG
 Am Kruppweid 1 · D - 46238 Bottrop
 Tel. (0 20 41) 10 19-0 · Fax 26 24 13
 (Unterschrift)