

DECLARATION OF PERFORMANCE  
according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

---

No 3412000

---

**MULTIPROOF**

---

Liquid applied water impermeable dispersion product with enhanced crack bridging ability at low temperatures (-20°C) and resistant against contact with chlorine water

---

**BOTAMENT GmbH & Co.KG**  
**Am Kruppwald 1**  
**D - 46238 Bottrop**

---

System 3

---

14891:2012

---

MPA TU Braunschweig  
0761

---

Declared performance/s:

Essential characteristic	Performance	System of assessment and verification of constancy of performance	Harmonised technical specification
<b>Initial tensile adhesion strength</b>	≥ 0,5 N/mm <sup>2</sup>	system 3	14891:2012
<b>Tensile adhesion strength after water contact</b>	≥ 0,5 N/mm <sup>2</sup>		
<b>Tensile adhesion strength after heat ageing</b>	≥ 0,5 N/mm <sup>2</sup>		
<b>Tensile adhesion strength after freeze-thaw cycles</b>	≥ 0,5 N/mm <sup>2</sup>		
<b>Tensile adhesion strength after contact with lime water</b>	no penetration		
<b>Waterproofing</b>	≥ 0,75 mm		
<b>Crack bridging ability at normal conditions</b>	NPD		
<b>Tensile adhesion strength after chlorine water contact</b>	≥ 0,5 N/mm <sup>2</sup>		
<b>Crack bridging ability at low temperatures (-5 °C)</b>	≥ 0,75 mm		
<b>Crack bridging ability at very low temperatures (-20°C)</b>	≥ 0,75 mm		

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

  
**BOTAMENT**  
SYSTEMBAUSTOFFE   
GmbH & Co. KG  
..... Am Kruppwald 1 • D - 46238 Bottrop  
Bottrop 03.04.2010 • Tel: 0204 24 11 10 • Fax 26 24 13

Dr. Oliver Wowra  
Leitung Technik