

**DECLARATION OF PERFORMANCE**  
according Annex III of the Regulation (EU) No 305/2011

Name of the product **BOTAMENT M 01**

No. **4400000**

1. Unique identification code of the product-type:

**EN 1504-3: ZA.1a**

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):

batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Product for Structural and non structural repair for concrete

Applying mortar by hand (3.1)

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**BOTAMENT GmbH & Co.KG**  
**Am Kruppwald 1**  
**D - 46238 Bottrop**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):

not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

System 2+

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified body Materialprüfungs- und Forschungsanstalt Karlsruhe (MPA Karlsruhe), identification number 0754, performed the initial inspection of the manufacturing plant and of factory production control and the continuous surveillance, assessment and evaluation of factory production control under system 2+ and issued:

Certificate of conformity of the factory production control 0754-CPD-07-0534

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:  
not relevant
9. Declared performance

Essential characteristics	Performance	Harmonised Technical specification
Compressive strength	class R2	EN 1504-3:2005
Chloride ion content	≤ 0,05 %	
Adhesive bond	≥ 0,8 MPa	
Restrained shrinkage/expansion	≥ 0,8 MPa	
Carbonation resistance	NPD	
Elastic modulus	NPD	
Thermal compatibility	≥ 0,8 MPa	
Skid Resistance	NPD	
Coefficient of thermal expansion	NPD	
Capillary absorption	≤ 0,5 kg.m <sup>-2</sup> .h <sup>-1/2</sup>	
Reaction to fire	class A1	
Dangerous substances	NPD	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra  
Leitung Technik

Bottrop, 07.05.2013

  
**BOTAMENT<sup>®</sup>**  
 SYSTEMBAUSTOFFE ■ ■ ■ ■  
 GmbH & Co. KG  
 Am Kruppwerk 10 19-0 • Fax 26 24 13  
 (Unterschrift) Bottrop