

DECLARATION OF PERFORMANCE

according Annex III of the Regulation (EU) No 305/2011

Name of the product **BOTAMENT[®] M 21 HP Speed**

No. 5081442

1. Unique identification code of the product-type:

EN 12004 C2 FTE S1

2. Type, batch or serial number or any other element allowing identification of the construction product as required pursuant to Article 11(4):
batch number: see packaging of the product

3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer:

Fast hardening improved cement adhesive for interior and external tiling

4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required pursuant to Article 11(5):

**BOTAMENT[®] GmbH & Co.KG
Am Kruppwald 1
D - 46238 Bottrop**

5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):
not relevant

6. System or systems of assessment and verification of constancy of performance of the construction product as set out in Annex V:

**System 3
System 4 (for reaction-to-fire regulations)**

7. In case of the declaration of performance concerning a construction product covered by a harmonised standard:

The notified testing laboratory Säurefliesner Vereinigung E.V., identification number 1212, performed the determination of the product-type on the basis of type testing under system 3 and issued: test report 66421401.101

The BOTAMENT GmbH & Co.KG carried out the reaction to fire classification according to the system 4 according to the Commission Decision 2010/81/EU.

8. In case of the declaration of performance concerning a construction product for which a European Technical Assessment has been issued:
not relevant
9. Declared performance


Essential characteristic	Performance	Harmonised technical specification
Reaction to fire	E	EN 12004:2007+A1:2012
Bond strength as		
Initial tensile adhesion strength	≥ 1,0 N/mm ²	
Early tensile adhesion strength	≥ 0,5 N/mm ²	
Durability of bond strength as:		
Tensile adhesion strength after water immersion	≥ 1,0 N/mm ²	
Tensile adhesion strength after heat ageing	≥ 1,0 N/mm ²	
Tensile adhesion strength after freeze-thaw cycles	≥ 1,0 N/mm ²	
Release of dangerous substances	accordance with 4.5 (EN12004)	

10. The performance of the product identified in points 1 and 2 is in conformity with the declared performance in point 9. This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra
Leitung Technik

Bottrop, 16.07.2018


BOTAMENT®
 SYSTEMBAUSTOFFE ■ ■ ■ ■
 GmbH & Co. KG
Am Kruggraben 11 · D - 46286 Bottrop
Tel. (0 20 41) 10 19-0 · Fax 26 24 19