

**DECLARATION OF PERFORMANCE**  
according Annex III of the Regulation (EU) No 305/2011  
amended by Commissions delegated Regulation (EU) No 574/2014

---

**No. 4521020**

---

**Unique identification code of the product-type:**

**BOTAMENT M 38**

---

**Intended use/es:**

Product for Structural and non structural repair for concrete  
Applying mortar by hand (3.1)  
Spraying concrete or mortar (3.3)  
Increasing cover to reinforcement with additional cementitious mortar or concrete (7.1)  
Replacing contaminated concrete (7.2)

---

**Manufacturer:**

**BOTAMENT GmbH & Co.KG**  
**Am Kruppwald 1**  
**D - 46238 Bottrop**

---

**System/s of AVCP:**

System 4 (For applications with low performance requirements in construction and civil engineering)  
System 4 (For applications that are subject to fire behavior regulations)

---

**Harmonised standard:**

EN 1504-3:2005  
DIN EN/TS 12390-9

---

**Notified body/ies:**

Materialprüfanstalt HARTL  
Kennnummer: A0093

---

**Declared performance/s:**

Essential characteristics	Performance	System of assessment and verification of constancy of performance	Harmonised Technical specification
Compressive strength	class R3	System 4	EN 1504-3:2005
Chloride ion content	≤ 0,05 %		
Adhesive bond	≥ 2,0 MPa		
Thermal compatibility Freeze-thaw	≥ 1,5 MPa		
Carbonation resistance <sup>1) 3)</sup>	passed		
Reaction to fire	Class A1		
CDF- Test method	≤ 0,200 kg/m <sup>2</sup>		DIN CEN/TS 12390-9

The performance of the product identified above is in conformity with the set of declared performance/s. This declaration of performance is issued, in accordance with Regulation (EU) No 305/2011, under the sole responsibility of the manufacturer identified above.

Signed for and on behalf of the manufacturer by:

Dr. Oliver Wowra  
Leitung Technik BOTAMENT

Bottrop, 30.03.20

